





LED Strobe Signal Light and Electric Horn Max.115dB

- By using the horn cover as a light globe, the size of the product has been reduced significantly
- Easy device customization with built in sound selection function, volume adjustment function and an SDcard slot for user inputted tones
- 31 available tones that can be selected for a variety of environments
- The user can select their own tones by inputting the MP3 file directly into the SDcard.
- 31 pre-recorded tones available via binary input
- Suitable for use in environments that require a tight seal and superior dust protection rated IP66
- Can be used in extreme environmental conditions such as the arctic where temperatures can reach -50°C
- Flashing rate : 60-80 flashes/min(steady/flashing mode selection available in built in switch)
- Materials : Horn-PC, Body-ABS
- Ambient operating temperature : -50°C to +60°C
- Protection Rating : IP66
- Certificates : CE Compliant, UL Listed
- Compliant with RoHS directive



Product Specifications

Voltage	Current	Sound Pattern and Volume	Certificates	Weight	Color
DC12V-24V	Max. 1.025A	• Bit Input : 5Ch(SDcard) • Binary Input : 31Ch • Warning Sounds : 115dB • MP3 Messages : 113dB	 	1.10kg	 R-Red  A-Amber  G-Green  B-Blue
AC110V-220V	Max. 0.360A			1.15kg	